

**NOTES:**

**ELECTRICAL:**



1. VOLTAGE RATING:125 VAC RMS
2. CURRENT RATING:1.5AMP
3. CONTACT RESISTANCE:100MILLIOHMS MAX
4. INSULATION RESISTANCE:1000 MEGOHMS MIN @500 VDC
5. DIELECTRIC STRENGTH:750 VAC RMS 60Hz, 1MIN

**ENVIRONMENTAL:**

1. STORAGE:-40° TO +85°
2. OPERATION:0° TO 70°

**MECHANICAL:**

1. HOUSING MATERIAL:PC
2. INSERT MATERIAL:FAME RETARDANCY PBT
3. PCB MATERIAL:FR-4 T=1.6mm
4. CONTACT MATERIAL:PHOSPHOR BRONZE  
STAMP PIN T=0.30mm
5. IDC CONTACT MATERIAL:PHOSPHOR BRONZE  
T=0.50mm WITH TIN PLATING
6. RJ45 JACK ;LIFE:750 TIMES MIN
7. IDC LIFE:200 TIMES MIN
8. WIRE:AWG 22-26

 <b>TRIAx</b>				Art. no.	157074
Material				Part Name	Cat6 UTP Keystone Jack 90°
Angles Projection	Size	Scale	Unit		
	A4	X:1	mm	ERP	Part No.
Sheet	1 OF 1	Version: A/0			